Model 102HEPA-Dry 12 Gallon

Number one choice of abatement professionals

The 102HEPA-D is a proven performer in the abatement industry. For over twenty years, it has earned the reputation as a true "work horse" by abatement, remediation and restoration professionals. A heavy-duty polyethylene tank with dump valve, rugged construction and long-life, commercial grade vacuum motor help make this model the toughest, most durable HEPA Vacuum in the market today.

Powerful Vacuum

A 2 Horsepower, 2 stage by-pass, 11.1 amp motor delivers 105" of waterlift and 110 CFM. Plenty of power for fast pick-up of wet and dry hazardous materials.

True 99.97% Type A Large Capacity HEPA Filter

Individually tested and certified to have a minimum efficiency of 99.97% at .3 microns in accordance with IEST-RP-CC001 test requirements.

Features:



High efficiency 2-ply enclosed, disposable paper filter bag acts as the primary filter to trap and hold dry material for easy handling and disposal. (B524253)



Complete HEPA Filter Assembly consisting of air seal gasket, polyester prefilter, spacer sleeve and Dacron filter bag (B160009)

Pullman-Holt HEPA Filter System



Air Seal Gasket - Provides tight air seal and prevents leakage.

HEPA Media - The filter is made from a single piece of high- grade HEPA media to eliminate the possibility of leaks. The pleats in the media are held open by corrugated aluminum separators for maximum airflow.

Spacer Sleeve – The purpose of the spacer sleeve is to space the Dacron bag away from the HEPA filter body so as to utilize the full area of the "Never Clog" Dacron bag.

Polyester Prefilter - This impact filter is about one inch thick and is attached to the inlet (bottom) surface of each HEPA filter. Its function is to provide final protection to the HEPA filter from premature failure due to clogging.

"Never Clog" Filter Bag - Sheds dirt and debris like a duck sheds water. Shakes clean to maintain maximum airflow.

PULLMAN-HOLT Part No. B700030 P512306 IEST-RP-CC001., Type A, Grade 6, 105 cfm This Hepa filter has been tested and is certified to have a minimum efficiency of 99.97% on .3 micron. Serial number: KK2258550 Penetration rate: ..022 .98 Pressure drop: www.pullmanholtcorp.com

Each Pullman-Holt HEPA filter is tested and certified to provide a minimum efficiency of 99.97% at .3 microns based on IEST-RP- CC001 test requirements.



PULLMAN-HOLT

Specifications

Style:	Dry
Horsepower:	2
Waterlift:	105"
CFM:	110
Recovery:	12 gallon
Recoverable Capacity:	1.75 bushel
Shipping Weight:	84 lbs.
Cord Length	25 feet
Motor Warranty:	1 year
Product Code:	B527038

Meets & exceeds EPA & OSHA standards

Accessories



Polyster prefilter B700017

Disposable paper filter bags B524253

B160009