

## T15000 3P HEPA Dust Extractor

Creating Clean Air for Construction, Abatement and Restoration



The most powerful 230V HEPA Dust Extractor on the market today. The greatly expanded pre-filter surface area acts as a built-in pre-separator providing superior cyclonic separation for long, uninterrupted service periods. The T15000 produces plenty of airflow to handle a single four-head grinder or two each three-head grinders. Clean air exhaust is guaranteed through four individually tested and certified HEPA filters. The intake port connects to a Y-connector where one or two 3" hoses can be connected. When used with one hose, up to 100-feet in length can be used. The out-port allows venting of the exhaust air away from the work area or outside of the building via a hose connection. Jet Pulse efficiently cleans the pre-filter without exposing operator to dust. The unique 72 foot Longopac® allows fast, drop-down, dust-free disposal into approximately 25 individually sealed bags. Comes with a 3", 33' hose, and a single 4" to double 3" Y connector.



When used with two 3-head grinders (up to 32" wide), a pre-separator should be connected between each grinder and the T15000 to achieve best results.



- Jet Pulse with easy reach lever: efficient, safe filter cleaning without exposing operator to dust.
- Relief Valve: protects turbine motor from overheating in the event of a blocked hose or clogged filter.
- Control Panel with one-touch start feature: protects from overloads.
- Cyclonic Chamber: separates/removes larger dust particles from the airstream before the air enters the pre-filter socks
- Adjustable steel clamps: provides tight air seal between top chamber and cyclone chamber.
- Four Individually Tested and Certified HEPA Filters: each filter provides a minimum efficiency of 99.99% at .3 microns
- Longopac®: 72 ft long plastic tube can be separated into approximately 25 individual sealed bags.
- Steel Frame with Longopac platform: supports the weight of filled Longopac bag..
- 4-inch casters w/brake: excellent mobility, stability and increased safety.



Coated Pre-Filter Socks:  
twenty-five multi layered



"Y" connector: for a  
single or dual hose  
application

### T15000 Specifications

CFM:	647
HP:	16
Amp:	42
Volt:	230
Water lift:	140
Weight:	905
Product Code:	201300403

Filter information  
4 HEPA Filters 108 (ft<sup>2</sup>), 99.99% at 0.3 microns